

# **EGC-A**Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 18/06/2015 Revision date: 22/07/2020 Supersedes version of: 20/07/2018

Version: 3.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : EGC-A

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only

### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Sidec

Industrieweg 10 2490 Balen - BELGIE T +32 14 81 50 01

safety@sidec.be - www.sidec.eu

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+32 70 245 245

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1 H317 Aquatic Chronic 3 H412

Full text of H statements : see section 16

### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP) : Warning

Hazardous ingredients : Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane; Formaldehyde,

oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; Hexamethylene

diacrylate; Trimethylolpropane triacrylate

Hazard statements (CLP) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P261 - Avoid breathing vapours, gas, mist, fume, spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

 ${\tt P280-Wear\ protective\ gloves/protective\ clothing/eye\ protection/face\ protection/hearing}$ 

protection.

P302+P352 - IF ON SKIN: Wash with plenty of soap, water.

23/07/2020 EN (English) 1/11

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### 2.3. Other hazards

Adverse physicochemical, human health and environmental effects

: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

### **SECTION 3: Composition/information on ingredients**

#### **Substances**

Not applicable

#### 3.2. **Mixtures**

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	30 – 60	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	(CAS-No.) 9003-36-5 (EC-No.) 500-006-8 (REACH-no) 01-2119454392-40	15 – 30	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Trimethylolpropane triacrylate	(CAS-No.) 15625-89-5 (EC-No.) 239-701-3 (EC Index-No.) 607-111-00-9	12 – 15	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317
Bis(isopropyl)naphthalene	(CAS-No.) 38640-62-9 (EC-No.) 254-052-6	8 – 10	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Hexamethylene diacrylate	(CAS-No.) 13048-33-4 (EC-No.) 235-921-9 (EC Index-No.) 607-109-00-8	3 – 4	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317
1-Methoxy-2-propyl acetate substance with a Community workplace exposure limit	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7 (REACH-no) 01-2119475791-29	0,02 – 0,05	Flam. Liq. 3, H226
SID-123-86-4 substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	0,02 - 0,05	Flam. Liq. 3, H226 STOT SE 3, H336
Ethyl acetate substance with a Community workplace exposure limit	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5 (REACH-no) 01-2119475103-46	0,02 – 0,05	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	( 5 ≤C < 100) Skin Irrit. 2, H315 ( 5 ≤C < 100) Eye Irrit. 2, H319

Full text of H-statements: see section 16

#### **SECTION 4: First aid measures**

### **Description of first aid measures**

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or First-aid measures after skin contact

rash occurs: Get medical advice/attention.

First-aid measures after eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### **Extinguishing media**

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

23/07/2020 EN (English) 2/11

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of : Toxic fumes may be released.

fire

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not eat, drink or smoke when using this product.

Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing gas,

mist, spray, vapours, fume.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed

out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

1-Methoxy-2-propyl acetate (108-65-6)		
EU	IOELV TWA (mg/m³)	275 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	550 mg/m³
EU	IOELV STEL (ppm)	100 ppm
Belgium	Limit value (mg/m³)	275 mg/m³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m³)	550 mg/m³
Belgium	Short time value (ppm)	100 ppm
France	VME (mg/m³)	275 mg/m³
France	VME (ppm)	50 ppm
France	VLE (mg/m³)	550 mg/m³
France	VLE (ppm)	100 ppm
Netherlands	Grenswaarde TGG 8H (mg/m³)	550 mg/m³
Netherlands	Grenswaarde TGG 8H (ppm)	100 ppm
United Kingdom	WEL TWA (mg/m³)	274 mg/m³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m³)	548 mg/m³

23/07/2020 EN (English) 3/11

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-Methoxy-2-propyl ac		
United Kingdom	WEL STEL (ppm)	100 ppm
SID-123-86-4 (123-86-4	)	
EU	IOELV TWA (mg/m³)	241 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	723 mg/m³
EU	IOELV STEL (ppm)	150 ppm
Belgium	Limit value (mg/m³)	238 mg/m³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m³)	712 mg/m³
Belgium	Short time value (ppm)	150 ppm
France	VME (mg/m³)	710 mg/m³
France	VME (ppm)	150 ppm
France	VLE (mg/m³)	940 mg/m³
France	VLE (ppm)	200 ppm
United Kingdom	WEL TWA (mg/m³)	724 mg/m³
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m³)	966 mg/m³
United Kingdom	WEL STEL (ppm)	200 ppm
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
Ethyl acetate (141-78-6	3)	
EU	IOELV TWA (mg/m³)	734 mg/m³
EU	IOELV TWA (ppm)	200 ppm
EU	IOELV STEL (mg/m³)	1468 mg/m³
EU	IOELV STEL (ppm)	400 ppm
Belgium	Limit value (mg/m³)	734 mg/m³
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m³)	1468 mg/m³
Belgium	Short time value (ppm)	400 ppm
France	VME (mg/m³)	1400 mg/m³
France	VME (ppm)	400 ppm
Netherlands	Grenswaarde TGG 8H (mg/m³)	734 mg/m³
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	1468 mg/m³
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (ppm)	400 ppm
USA - ACGIH	ACGIH TWA (ppm)	400 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Materials for protective clothing : protective clothing
Hand protection : Protective gloves
Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment



Environmental exposure controls : Avoid release to the environment.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : No data available
Odour : No data available

23/07/2020 EN (English) 4/11

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Odour threshold	:	No data available
рН	:	No data available
Relative evaporation rate (butylacetate=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Not applicable
Vapour pressure	:	No data available
Relative vapour density at 20 °C	:	No data available
Relative density	:	No data available
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	450 – 590 mPa⋅s
Explosive properties	:	No data available
Oxidising properties		No data available
Explosive limits	:	No data available

### 9.2. Other information

No additional information available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Stable under recommended handling and storage conditions (see section 7).

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Can react violently with alkalis, as well as a lot of organic products such as alcohols and amines. Extremely high or low temperatures.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane (25068-38-6)			
LD50 oral rat	11400 mg/kg		
LD50 dermal rat	2000 mg/kg		
Formaldehyde, oligomeric reaction products	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)		
LD50 oral rat	> 2000 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
Bis(isopropyl)naphthalene (38640-62-9)			
LD50 oral rat	4130 mg/kg bodyweight (Rat; OECD 401: Acute Oral Toxicity; Experimental Value)		
LD50 dermal rat	> 4500 mg/kg (Rat; Experimental value; OECD 402: Acute dermal toxicity)		
LC50 inhalation rat (mg/l)	> 5,64 mg/l/4h (Rat; Experimental value)		
1-Methoxy-2-propyl acetate (108-65-6)			
LD50 oral rat	6190 mg/kg bodyweight (Equivalent to or corresponding to OECD 401, Rat, Male / Female, Experimental value, Oral)		
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Equivalent to or corresponding to OECD 402, Rabbit, Male / female. Experimental value. Dermal)		

23/07/2020 EN (English) 5/11

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SID-123-86-4 (123-86-4)		
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent to or corresponding to OECD 423, Rat, Male / Female, Experimental value, Oral)	
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent to or corresponding to OECD 402, Rabbit, Male / female, Experimental value, Dermal)	
Ethyl acetate (141-78-6)		
LD50 oral rat	10200 mg/kg bodyweight (Equivalent to or corresponding to OECD 401, Rat, Female, Experimental value, Oral)	
LD50 dermal rabbit	> 20000 mg/kg bodyweight (24 hours cuff method, 24 hours, Rabbit, Male, Experimental value, Dermal)	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
STOT-single exposure	: Not classified	
STOT-repeated exposure	: Not classified	
Aspiration hazard	: Not classified	

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

57 5		
Phenol, 4,4'-(1-methylethylidene)b	is-, polymer with 2-(chloromethyl)oxirane (25068-38-6)	
LC50 fish 1	1,3 mg/l	
EC50 Daphnia 1	2,1 mg/l	
NOEC chronic crustacea	0,3 mg/l	
Formaldehyde, oligomeric reaction	n products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
LC50 fish 1	2,54 mg/l	
EC50 Daphnia 1	2,55 mg/l 202 Daphnia sp. Acute Immobilization Test and Reproduction Test	
1-Methoxy-2-propyl acetate (108-6	5-6)	
LC50 fish 1	100 – 180 mg/l (OECD 203: Fish: acute toxicity study, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)	
EC50 Daphnia 1	> 500 mg/l (EU method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)	
SID-123-86-4 (123-86-4)		
LC50 fish 1	18 mg/l (Equivalent to or corresponding to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)	
EC50 Daphnia 1	44 mg/l (48 h, Daphnia sp., Static system, Fresh water, Experimental value)	
Ethyl acetate (141-78-6)		
LC50 fish 1	230 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)	
EC50 Daphnia 1	154 mg/l (48 h, Daphnia magna, Literature)	

### 12.2. Persistence and degradability

Bis(isopropyl)naphthalene (38640-62-9)		
Persistence and degradability	Photolysis in the air. Water : Not biodegradable. Separation by sedimentation. easily degradable in the soil.	
ThOD	2,41 g O <sub>2</sub> /g substance	
1-Methoxy-2-propyl acetate (108-65-6)		
Persistence and degradability	Readily biodegradable in water. easily degradable in the soil.	
SID-123-86-4 (123-86-4)		
Persistence and degradability	Readily biodegradable in water.	
ThOD	2,21 g O₂/g substance	
BOD (% of ThOD)	0,46	
Ethyl acetate (141-78-6)		
Persistence and degradability	easily degradable in the soil. Readily biodegradable in water.	

23/07/2020 EN (English) 6/11

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acetate (141-78-6)	
Biochemical oxygen demand (BOD)	0,293 g O₂/g substance
Chemical oxygen demand (COD)	1,69 g O <sub>2</sub> /g substance
ThOD	1,82 g O <sub>2</sub> /g substance

#### 12.3. Bioaccumulative potential

12.3. Bioaccumulative potential			
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane (25068-38-6)			
Partition coefficient n-octanol/water (Log Pow)	2,64 – 3,78		
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)			
Partition coefficient n-octanol/water (Log Pow)	3,3		
Bis(isopropyl)naphthalene (38640-62-9)			
BCF fish 1	370 – 3930 (BCF; 8 weeks; Cyprinus carpio)		
Partition coefficient n-octanol/water (Log Pow)	6,08 (calculated value; US EPA)		
Bioaccumulative potential	strong. Bioaccumulative potential.		
1-Methoxy-2-propyl acetate (108-65-6)	1-Methoxy-2-propyl acetate (108-65-6)		
Partition coefficient n-octanol/water (Log Pow)	1,2 (Experimental value, Equivalent to or corresponding to OECD 117, 20 ° C)		
Bioaccumulative potential	Low bioaccumulation potential.		
SID-123-86-4 (123-86-4)			
BCF fish 1	15,3 (calculated value)		
Partition coefficient n-octanol/water (Log Pow)	2,3 (Test data, OECD 117: Partition coefficient (n-octanol / water), HPLC method, 25 ° C)		
Bioaccumulative potential	Potential to bioaccumulate is low.		
Ethyl acetate (141-78-6)			
BCF fish 1	30 (3 day (s), Leuciscus idus, Static system, Experimental value)		

# Bioaccumulative potential 12.4. Mobility in soil

1-Methoxy-2-propyl acetate (108-65-6)		
Surface tension	29,4 mN/m (20 °C, 100 vol %, EU-methoe A.5)	
Partition coefficient n-octanol/water (Log Koc)	0,264 (log Koc, QSAR)	
Ecology - soil	strong. Mobile.	
SID-123-86-4 (123-86-4)		
Surface tension	0,0163 N/m (20 °C)	
Partition coefficient n-octanol/water (Log Koc)	1,268 – 1,844 (log Koc, SRC PCKOCWIN v2.0, QSAR)	
Ecology - soil	little. Adsorption in soil.	
Ethyl acetate (141-78-6)		
Surface tension	0,024 N/m (20 °C)	
Ecology - soil	little. Adsorption in soil.	

Low bioaccumulation potential.

0,68 (experimental value, EPA OPPTS 830.7560, 25 °C)

### 12.5. Results of PBT and vPvB assessment

Partition coefficient n-octanol/water (Log Pow)

No additional information available

#### 12.6. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Ecology - waste materials : Avoid release to the environment.

European List of Waste (LoW) code : 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE

(MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES,

SEALANTS AND PRINTING INKS

# SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR) : 3082 UN-No. (IMDG) : 3082

23/07/2020 EN (English) 7/11

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

UN-No. (IATA) : 3082 UN-No. (ADN) : 3082 UN-No. (RID) : 3082

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.

Proper Shipping Name (ADN) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Proper Shipping Name (RID) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport document description (ADR) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy

derivatives), 9, III, (E)

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy

derivatives), 9, III

### 14.3. Transport hazard class(es)

#### **ADR**

Transport hazard class(es) (ADR) : 9
Danger labels (ADR) : 9



#### **IMDG**

Transport hazard class(es) (IMDG) : 9
Danger labels (IMDG) : 9



### IATA

Transport hazard class(es) (IATA) : 9
Danger labels (IATA) : 9



### ADN

Transport hazard class(es) (ADN) : 9
Danger labels (ADN) : 9



#### RID

Transport hazard class(es) (RID) : 9
Danger labels (RID) : 9

23/07/2020 EN (English) 8/11

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



14.4. **Packing group** 

Packing group (ADR) : 111 Packing group (IMDG) : 111 : 111 Packing group (IATA) Packing group (ADN) : 111 Packing group (RID) : III

#### **Environmental hazards**

Dangerous for the environment : No : No Marine pollutant

Other information : No supplementary information available

#### Special precautions for user 14.6.

#### - Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 601

Limited quantities (ADR) : 51 Excepted quantities (ADR) : E1

: P001, IBC03, LP01, R001 Packing instructions (ADR)

Special packing provisions (ADR) : PP1 : MP19 Mixed packing provisions (ADR) Portable tank and bulk container instructions : T4

(ADR)

Portable tank and bulk container special : TP1, TP29

provisions (ADR)

Tank code (ADR) : LGBV Vehicle for tank carriage : AT Transport category (ADR) : 3 Special provisions for carriage - Packages : V12

(ADR)

Special provisions for carriage - Loading,

unloading and handling (ADR)

Hazard identification number (Kemler No.)

Orange plates

: CV13

: 90

3082

90

Tunnel restriction code (ADR) : E EAC code : •3Z

### - Transport by sea

Special provisions (IMDG) : 274, 335 Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01 : PP1 Special packing provisions (IMDG) IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T4 Tank special provisions (IMDG) : TP2, TP29 : F-A EmS-No. (Fire) : S-F EmS-No. (Spillage) Stowage category (IMDG) : A

- Air transport

PCA Excepted quantities (IATA) : E1

23/07/2020 EN (English) 9/11

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PCA Limited quantities (IATA) : Y964 PCA limited quantity max net quantity (IATA) : 30kgG PCA packing instructions (IATA) : 964 PCA max net quantity (IATA) : 450L CAO packing instructions (IATA) 964 CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197

ERG code (IATA) : 9L

- Inland waterway transport

: M6 Classification code (ADN)

Special provisions (ADN) : 274, 335, 61

Limited quantities (ADN) : 5 L Excepted quantities (ADN) : E1 Carriage permitted (ADN) : T Equipment required (ADN) : PP Number of blue cones/lights (ADN) : 0 Carriage prohibited (ADN) : No Not subject to ADN : No

- Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 601

Limited quantities (RID) : 5L Excepted quantities (RID) · F1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1 Mixed packing provisions (RID) : MP19 Portable tank and bulk container instructions : T4

(RID)

Portable tank and bulk container special

provisions (RID)

: TP1, TP29

Tank codes for RID tanks (RID) : LGBV Transport category (RID) : 3 Special provisions for carriage - Packages : W12

(RID)

Special provisions for carriage - Loading,

unloading and handling (RID)

: CW13, CW31

Colis express (express parcels) (RID) : CE8 Hazard identification number (RID) : 90 Carriage prohibited (RID) : No

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. **EU-Regulations**

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

#### 15.1.2. **National regulations**

### Germany

: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1) Regulatory reference

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

23/07/2020 EN (English) 10/11

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SZW-lijst van mutagene stoffen

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting

. None of the components are nated

giftige stoffen – Vruchtbaarheid

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling

: None of the components are listed

Denmark

Recommendations Danish Regulation

: Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the

product

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### **SECTION 16: Other information**

#### Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

23/07/2020 EN (English) 11/11